

DYNA FLEX INC.

SEWER CLEANING

SWRO (ORANGE)

2500 PSI



Recommended For: Use on high pressure sewer cleaning equipment.

Innercore: Orange seamless polyolefin tube

Reinforcement: Two braids of high tensile synthetic fiber

Cover: Bonded orange high abrasion mold and fungus resistant polyether-urethane featuring an anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWRO-12	3/4	19.05	1.165	29.59	2,500	172	6,250	431	4	29.0
SWRO-16	1	25.40	1.44	36.58	2,500	172	6,250	431	6	40.0
SWRO-20	1-1/4	31.75	1.80	45.72	2,500	172	6,250	431	8	59.0

**MAIN OFFICE
DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.**

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com REV B, Jan 1, 2011

DYNA FLEX

SEWER CLEANING

**SWRBLUE (BLUE)
3000 PSI**



Recommended For: Use on high pressure sewer cleaning equipment.

Innecore: Orange seamless polyolefin tube

Reinforcement: Two braids of high tensile synthetic fiber

Cover: Bonded blue high abrasion mold and fungus resistant polyether-urethane featuring an anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWRBLUE-12	3/4	19.05	1.16	29.59	3000	207	7500	517	4	32.0
SWRBLUE-16	1	25.40	1.44	36.58	3000	207	7500	517	6	40.0

**MAIN OFFICE
DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.**

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.sewerjettinghose.com E-mail: sales@flexinc.com REV B, Jan 1,
2011

DYNA FLEX

SEWER JETTING

SWRG (GREEN) 4000 PSI



Recommended For: Use on high pressure sewer jetting equipment.

Innercore: Neutral color seamless polyester tube

Reinforcement: One and two braid high tensile synthetic fiber

Cover: Bonded green high abrasion mold and fungus resistant polyester-urethane with a anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWRG-02*	1/8	3.18	.305	7.75	4000	276	10000	689	1/2	2.5
SWRG-03	3/16	4.76	.405	10.29	4000	276	10000	689	3/4	5.5
SWRG-04	1/4	6.35	.505	12.83	4000	276	10000	689	1-1/4	7.0
SWRG-06	3/8	9.53	.720	18.29	4000	276	10000	689	2	10.5
SWRG-08	1/2	12.70	.810	20.57	4000	276	10000	689	3	15.0

* Single Braid

**MAIN OFFICE
DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.**

PHONE: (440) 946-0719 FAX: (440) 946-4620 TOLL FREE: (800) 525-8463
www.sewerjettinghose.com E-Mail: sales@flexinc.com REV B, Jan 1, 2011